



UVETT SEALER PG 15/2

UF5942100

DESCRIPTION:

Uvett Sealer PG 15/2 is a one component UV-light cured clear sealer, suitable for roller coater application on most wood substrates. This product is extremely fast curing and easy to sand. Topcoat with one of AcromaPro's UV topcoats. Uvett Sealer PG 15/2 provides good build and good adhesion to wood. This product is free from Styrene. Minimized risks for skin irritation.

PRODUCT DATA:

Color:	Clear	VOC (as packaged, maximum, less water and exempt solvents):	0.01 lb/gal, 1.92 g/l
Solids % by Vol.:	99.8 % (Theoretical)	VOC (emitted):	0.01 lb/gal, 1.92 g/l
Solids % by Wt.:	99.7 % (Theoretical)	Lbs. VHAPs / Lbs. Solids:	0.00
Weight / Gal.:	9.48 lb	Flash Point (PMCC):	Does not flash
Viscosity 25°C / 77°F:	Brookfield.: 1350 cps	Photo Chemically Reactive:	YES
Viscosity 25°C / 77°F:		Shelf Life:	3 months (at 15-25° C / 59°-77°)

MIXING / APPLICATION:

Working Temp: >18° C, 65° F substrate, coating and air
Hardener: N/A
Catalyzation: N/A
UV Cure: Min UV Dose (280 – 320 nm)>300 mj / cm².
Working Temp: >18° C, 65° F substrate, coating and air
Pot Life: N/A
Mixing: Mix thoroughly to ensure uniform consistency.
Reducer: N/A
Application: Roller Coater at 10 to 50 g / m².
Surface Prep: Substrate should be clean and free of grease and oil. Moisture content of the wood should be between 6%-8%. Sand 150 grit on open grain and 180 grit on closed grain wood.
Use Directions: For interior use only. Mix thoroughly before application.

DRYING TIMES:

UV Cure	Mercury lamps >300 mj / cm ²
---------	---

TESTING: Due to the wide variety of substrates, surface preparation methods, application methods, and environments, the customer should test the complete system for adhesion, compatibility and performance prior to full scale application.

FOR INDUSTRIAL SHOP APPLICATION: Thoroughly review Safety Data Sheet (SDS) for safety information and cautions prior to using this product. For Regulatory compliance data (i.e. VOC, HAPS, etc.), obtain an Environmental Data Sheet (EDS) prior to using the product. Regulatory documents are available from your local distributor or representative. Please direct any questions or comments to 1-800-524-5979.

NOTE: Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, AcromaPro cannot make any warranties as to the end result.